







Visual Inspection & Locating

SeeSnake Reel and Camera Selection

						
Applications	Toilets/Sinks/Lines	Main Drain Lines	Main Drain Lines	Industrial	Industrial	Industrial
Page Number	11.8	11.7	11.7	11.6	11.6	11.6
Line Capacity	1½" to 3"/3.2 to 7.6 cm	1½" to 4"/3.8 to 10.2 cm	1½" to 4"/3.8 to 10.2 cm	1½" to 6"/3.8 to 15 cm	2" to 12"/5 to 30 cm	2" to 12"/5 to 30 cm
Maximum Run	30'/9.14 m	100'/30.48 m	100'/30.48 m	200'/61 m	325'/99 m	325'/99 m
Sonde Transmitter	Optional 512Hz	512 Hz	512 Hz	512 Hz	512 Hz	512 Hz
Distance Measurement	–	Built In Counter	–	CountPlus	CountPlus	CountPlus
Mechanical						
Weight (Excl. Monitor)	7.3lbs/3.3 kg	13lbs/5.9 kg (reel)	11lbs/5.5 kg (reel)	24.5 lbs./11.1 kg	43 lbs./19.5 kg	43 lbs./19.5 kg
Reel & Frame Diameter	12.75"/32 cm	16"/40 cm	24"/61 cm	20"/51 cm	32"/81 cm	32"/81 cm
Camera Diameter	.87"/22 mm	1.18"/30 mm	1.18"/30 mm	1.18"/30 mm	1.365"/35 mm	1.365"/35 mm
Camera Length	.87"/22 mm	1.68"/42 mm	1.68"/42 mm	1.68"/42 mm	1.82"/45 mm	1.82"/45 mm
Push Cable Diameter	.33"/8.3 mm	0.26"/6.6 mm	0.26"/6.6 mm	0.31"/8 mm	0.44"/11 mm	0.44"/11 mm
Environmental						
Operating Temperature	-4° to 104°F	32° to 104°F	32° to 104°F	32° to 104°F	32° to 104°F	32° to 104°F
Waterproof Depth	266'/81 m	330'/100 m	330'/100 m	330'/100 m	330'/100 m	330'/100 m
Video	510 x 496	768 x 494	768 x 494	768 x 494	768 x 494	768 x 494
Number Of Pixels	250	410	410	410	410	410
Lighting	3 Luxeon LEDs	6 Luxeon LEDs	6 Luxeon LEDs	6 Luxeon LEDs	6 Luxeon LEDs	6 Luxeon LEDs
Camera	All SeeSnake Reels and Cameras are Compatible with All SeeSnake Monitors					

Color Monitors and Video Recorders

					
Page Number	11.4	11.4	11.4	11.5	11.5
Recording Capability	View only / *DVDBase	Built in DVD	View only / *DVDBase	Built in DVD	Built in VHS
Screen Size	10.4"	4.3" OLED/5.7" LCD	5.7"	10.4"	10.4"
Screen Type	LCD	OLED/LCD	LCD	LCD	LCD
Battery	1 or 2 18V LI	18V LI	18V LI	–	–
Battery Runtime	4.5 hrs (2 batteries)	2.5 hrs	5 hrs	–	–
Integrated Line Trace	Yes	Yes	Yes	–	–
Sonde Control 512Hz	Push Button	Push Button	Push Button	Analog	Analog
Lighting Controls	10-Level Digital	10-Level Digital	10-Level Digital	Analog	Analog
Screen Operating Range	14°F to 122°F	-30°F to 130°F	-4° to 158°F	14°F to 122°F	32°F to 104°F
Recorder Operating Range	–	40°F to 95°F	–	40°F to 95°F	0°F to 140°F
Resolution	640 x 480	320 x 240	320 x 240	640 x 480	640 x 480
DVDBase Recorder	*Record inspection footage from any current or previous SeeSnake monitor with a video output. See page 11.5.				